



Aprisa SR+

SMART, SECURE POINT-TO-POINT RADIO
VHF, 220 MHz, and UHF licensed bands

[DATASHEET \[ETSII\]](#)

Smart, secure, industry-leading speed licensed point-to-point for linking and backhaul of industrial monitoring and control – now with 256 QAM

- **High capacity:** to meet the growing number of data-intensive applications in the SCADA environment, the Aprisa SR+ PTP provides data rates of up to 1,024 kbit/s full duplex in 100 kHz licensed channels.
- **Secure:** with its defense in depth approach, including AES encryption, authentication, address filtering and user access control including RADIUS, the Aprisa SR+ PTP protects against vulnerabilities and malicious attacks.
- **Future-proof:** the Aprisa SR+ PTP supports dual serial and dual Ethernet ports in a single, compact form factor, designed to cryptographically secure legacy serial, protect existing device investment, and enable new applications. Old and new application protocols can be run side by side.
- **Advanced L2 / L3 capabilities:** selectable L2 bridge, L3 router, or advanced gateway router combination L2 / L3 modes with VLAN, QoS, NAT, and filtering attributes to maximize capacity in constrained bandwidth and prioritize mission critical traffic while meeting tough security and IP network policy imperatives.
- **Flexible interfaces:** the data interfaces can be configured for serial or Ethernet operation; a range of options are supported, including two serial and two Ethernet, one serial and three Ethernet, or four Ethernet ports. Support for NMEA GPS receiver option.
- **Link efficiency:** Adaptive Coding and Modulation (ACM) and forward error correction maintains the integrity of the wireless connection while an effective channel access scheme and IP routing ensures efficient transfer of data across a Aprisa SR+ PTP link. Automatic Transmit Power Control maintains the minimum transmit power required for effective communications enhancing both frequency reuse and power savings. Advanced payload and Ethernet / IP / TCP / UDP header compression.
- **Reliable and robust:** the Aprisa SR+ PTP requires no manual component tuning and maintains its performance over a wide temperature range using full specification industrially rated components and shared Aprisa family heritage.
- **Easily managed:** an easy to use GUI supports local element management via HTTPS and remote element management over the air and SNMP support allows network-wide monitoring and control via a variety of supported third party network management systems.

Applications

- Electricity grid: distribution automation control and protection in MV / HV distribution / transmission
- Smart grid, DA, DFA, DER, cap bank control
- Oil & Gas: production metering, lift pump automation
- AMI / AMR: high density data concentrator backhaul
- Renewables: wind farm, tidal, hydro automation
- Water and wastewater: flow, level, pressure modulation automation and pump status
- Ultra low latency for feeder protection – 6 ms at 100 kHz and 8 ms at 50 kHz

Aprisa SR+

SMART, SECURE POINT-TO-POINT RADIO

DATASHEET [ETSI] VHF, 220 MHZ, AND UHF LICENSED BANDS



Specifications

General	
Network Topology	Point-To-Point (PTP) Full Duplex
Network Integration	Serial and Ethernet (router or bridge mode)

Protocols	
Ethernet	IEEE 802.3, 802.1d/q/p
Serial	Legacy RS-232 transport, SLIP and Terminal Server support
Wireless	Proprietary
SCADA	Transparent to all common SCADA protocols such as Modbus, IEC 60870-5-101/104, DNP3 or similar

Radio	Frequency Band (MHz)	Tuning Range (MHz)	Tune Step (kHz)
Frequency Range	135	135 – 175	0.625
	220 ^[2]	215 – 240 ^[2]	0.625 ^[2]
	320	320 – 400	6.25
	400	400 – 470	1.25
	450	450 – 520	6.25
Channel Size	12.5 kHz, 20 kHz, 25 kHz, 50 kHz and 100 kHz ^[2] software selectable		
Duplex	Dual frequency full-duplex		
Frequency Stability	± 0.5 ppm		
Frequency Aging	< 1 ppm / annum		

Transmitter	
Max Peak Envelope Power (PEP)	10.0 W (+40 dBm)
Average Power Output	256 QAM 0.01 – 2.0 W (+10 to +33 dBm, in 1 dB steps)
	64 QAM 0.01 – 2.5 W (+10 to +34 dBm, in 1 dB steps)
	16 QAM 0.01 – 3.2 W (+10 to +35 dBm, in 1 dB steps)
	QPSK 0.01 – 5.0 W (+10 to +37 dBm, in 1 dB steps)
	4-CPFSK 0.01 – 10.0 W (+10 to +40 dBm, in 1 dB steps) ^[2]
Adjacent Channel Power	< -60 dBc
Transient Adjacent Channel Power	< -60 dBc
Spurious Emissions	< -37 dBm
Attack Time	< 1.5 ms
Release Time	< 0.5 ms
Data Turnaround Time	< 2 ms
Emission Designator	Contact Aviat Networks for Emission Reports.

Aprisa SR+

SMART, SECURE POINT-TO-POINT RADIO

DATASHEET [ETSI] VHF, 220 MHz, AND UHF LICENSED BANDS



Receiver			12.5 kHz	20 kHz	25 kHz	50 kHz	100 kHz
Sensitivity (BER < 10 ⁻⁶)	min coded	256 QAM ^[4]	-95 dBm	-91 dBm	-91 dBm	-88 dBm	-85 dBm
	max coded	64 QAM	-103 dBm	-99 dBm	-99 dBm	-96 dBm	-93 dBm
	max coded	16 QAM	-110 dBm	-107 dBm	-107 dBm	-104 dBm	-101 dBm
	max coded	QPSK	-115 dBm	-112 dBm	-112 dBm	-109 dBm	-106 dBm
	min coded	4-QPSK	-113 dBm	-110 dBm	-110 dBm	-107 dBm	-104 dBm
Adjacent Channel Selectivity			>-47 dBm	>-37 dBm	>-37 dBm	>-37 dBm	>-37 dBm
			^[1] [>48 dB]	[>58 dB]	[>58 dB]	[>58 dB]	[>58 dB]
Co-Channel Rejection	max coded	QPSK	>-10 dB				
Co-Channel Rejection	min coded	256 QAM	>-26 dB				
Intermodulation Response Rejection			>-35 dBm [>60 dB ^[1]]				
Blocking or Desensitisation			>-17 dBm [>78 dB ^[1]]				
Spurious Responce Rejection			>-32 dBm [>63 dB ^[1]]				

Modem		12.5 kHz	20 kHz	25 kHz	50 kHz	100 kHz
Gross Data Rate	256 QAM ^[4]	80 kbit/s	112 kbit/s	160 kbit/s	288 kbit/s	512 kbit/s
	64 QAM	60 kbit/s	84 kbit/s	120 kbit/s	216 kbit/s	384 kbit/s
	16 QAM	40 kbit/s	56 kbit/s	80 kbit/s	144 kbit/s	256 kbit/s
	QPSK	20 kbit/s	28 kbit/s	40 kbit/s	72 kbit/s	128 kbit/s
	4-QPSK	9.6 kbit/s	9.6 kbit/s	19.2 kbit/s	38.4 kbit/s	76.8 kbit/s
Forward Error Correction	Variable length concatenated Reed Solomon plus convolutional code					
Adaptive Burst Support	Adaptive Coding and Modulation					

Security	
Data Encryption	256, 192 or 128 bit AES
Data Authentication	CCM

Interfaces	
Ethernet Ports	RJ45 10/100Base-T auto-neg MDI/MDIX
Serial Ports	RJ45 RS-232 Additional RS-232 / RS-485 port via USB converter (optional)
GPS Receiver	Support for optional USP connect GPS receiver
Management	1 x USB micro type B (device port) 1 x USB standard type A (host port)
Antenna	2 x TNC 50 ohm female
Alarm I/O	1 x RJ45 Alarm I/O interface 2 x inputs + 2 x outputs
LEDs	Status: OK, MODE, AUX, TX, RX Diagnostics: RSSI, traffic port status
Test Button	Toggles LEDs between diagnostics / status

Aprisa SR+

SMART, SECURE POINT-TO-POINT RADIO

DATASHEET [ETSI] VHF, 220 MHz, AND UHF LICENSED BANDS



Product Options (specified at order)	
Data Port Configuration Options	2 x Ethernet ports + 2 serial ports 3 x Ethernet ports + 1 serial port 4 x Ethernet ports
Protected Station Options	Providing hot-swappable / hot-standby redundant hardware switching (13.8 VDC or 48 VDC)
Power	
Input Voltage	Radio 10 – 30 VDC negative earth
Receive	All bands except 320 MHz < 3 W (217 mA at 13.8 VDC)
	320 MHz < 7 W (507 mA at 13.8 VDC)
Transmit	135 and 220 MHz < 26 W (1884 mA at 13.8 VDC)
	400 and 450 MHz < 28 W (2028 mA at 13.8 VDC)
	320 MHz < 35 W (2536 mA at 13.8 VDC)
Mechanical	
Dimensions (not including connectors)	Radio 210 mm (W) x 130 mm (D) x 41.5 mm (H) 8.27" (W) x 5.12" (D) x 1.63" (H)
	Protected Station 434 mm (W) x 372 mm (D) x 88.9 mm (H) 2 RU 17.1" (W) 14.6" (D) 3.5" (H)
Weight	Radio 1.25 kg (2.81 lbs)
Mounting	Wall, Rack or DIN rail
Environmental	
Operating Temperature	-40 to +70 °C
Humidity	Maximum 95 % non-condensing
Management & Diagnostics	
Local Management	SSH and HTTP/S web servers with full control / diagnostics Partial diagnostics via LEDs and test button Software upgrade from PC or USB flash drive
Remote Element	SSH and HTTP/S over-the-air remote element management with control / diagnostics Network software upgrade over-the-air
Network	SNMPv2 and SNMPv3 security support for integration with external network management systems

Aprisa SR+

SMART, SECURE POINT-TO-POINT RADIO

DATASHEET [ETSI] VHF, 220 MHZ, AND UHF LICENSED BANDS



Compliance		
RED Compliance		Tested in accordance with the Radio Equipment Directive 2014/53/EU [3]
RF	12.5 kHz	EN 300 113
	25 kHz, 50 kHz and 100 kHz	EN 302 561 [5]
EMC		EN 301 489-1, EN 301 489-55
Safety		EN/UL/IEC 62368-1, CB Certified, UL listed
Hazardous Location		Class 1 division 2
Environmental		EN 300 019-2-3 Class 3.4, Ingress Protection IP51
Electric Substation		IEEE 1613 Class 2 and IEC 61850-3

Notes:

[1] The receiver figures are shown in typical fixed interference dBm values and dB values [in brackets] relative to the sensitivity. Relative values are given for QPSK modulation and max coded FEC. Refer to the Aprisa SR+ User Manual for a complete list of modulation and coding levels.

[2] Please consult Aviat Networks for availability

[3] 100 kHz subject to EU RED verification

[4] For 256 QAM on 100 kHz channel size, please consult Aviat Networks for availability

[5] 50 kHz, RX compliance to 64 QAM

Disclaimer

This material is for informational purposes only and does not constitute a legal obligation to deliver any product, feature or functionality and should not be relied upon in making purchasing decisions. All specifications are subject to change without notice. The development, release and timing of any features or functionality described for our products is at Aviat Networks' sole discretion.

For details of availability, Please contact your Aviat Networks Sales Representative.

Aviat, Aviat Networks and the Aviat logo are trademarks or registered trademarks of Aviat Networks, Inc.
Copyright © Aviat Networks, Inc. [2024] All Rights Reserved. Data subject to change without notice.